

# HX260



HX260 with options

## HX260 Technical Data

|                     |                              |
|---------------------|------------------------------|
| Weight              | 485 kg                       |
| Voltage             | 230 V Mono / 230 V - 3 Phase |
|                     | 400 V - 3 Phase              |
| Dust suction outlet | 100 mm                       |
|                     | + 60mm on sawguard           |

|                               |                  |
|-------------------------------|------------------|
| <b>Saw</b>                    |                  |
| Saw rotation speed            | 4500 RPM         |
| Diameter saw blade and bore   | 250 x 30 mm      |
| Cutting depth at 90°          | 85 mm            |
| Cutting depth at 45°          | 55 mm            |
| Dimensions cast iron table    | 1077 x 273 mm    |
| Dimensions sliding table      | 1450 mm x 320 mm |
| Cutting length                | 1200 mm          |
| Cutting width parallel fence  | 600 mm           |
| Motor power 3 phase (S6)      | 3 kW / 4 hp      |
| Motor power single phase (S6) | 2,2 kW / 3 hp    |

|  |                 |
|--|-----------------|
| <b>Spindle</b>                         |                 |
| Spindle rotation speed machine 3 phase | 3000 / 6000 RPM |
| Spindle rotation speed single phase    | 6000 RPM        |

|   |               |
|---|---------------|
| Diameter spindle arbor                                    | 30 mm         |
| Capacity spindle arbor                                    | 122 mm        |
| Travel  | 140 mm        |
| Dimensions table opening                                  | 180 mm        |
| Motor power 3 phase (S6)                                  | 3 kW / 4 hp   |
| Motor power single phase (S6)                             | 2,2 kW / 3 hp |
| For heavy milling tools the electronic brake is mandatory |               |

|                               |                 |
|-------------------------------|-----------------|
| <b>Planer-Thicknesser</b>     |                 |
| Total length planer tables    | 1320 mm         |
| Height capacity thicknesser   | 230 mm          |
| Diameter cutter block         | 70 mm           |
| Number of knives              | 3               |
| Dimensions knives             | 260 x 25 x 3 mm |
| Planer thicknesser width      | 260 mm          |
| Max. depth of cut             | 4 mm            |
| Feeding speed                 | 6 m/min         |
| Cutter block rotation speed   | 5500 RPM        |
| Motor power 3 phase (S6)      | 3 kW / 4 hp     |
| Motor power single phase (S6) | 2,2 kW / 3 hp   |

|                          |                   |
|--------------------------|-------------------|
| <b>Mortiser (Option)</b> |                   |
| Chuck                    | 0 - 16 mm         |
| Travel                   | 165 x 140 x 85 mm |

